



Bobcat®

Utility Vehicles UV34 and UV34XL



One Tough Animal®

SPECIFICATIONS



Vehicle	UV34 Diesel	UV34XL Diesel	UV34 Gas	UV34XL Gas
Engine				
Engine Model	Diesel	Diesel	1000CC Dual	1000CC Dual
Engine Cooling	Liquid	Liquid	Liquid	Liquid
Emissions Tier (EPA)	Tier 4	Tier 4	-	-
Engine Fuel	Diesel	Diesel	Gasoline EFI	Gasoline EFI
Horsepower	23.5 hp (17.5 kW)	23.5 hp (17.5 kW)	39.9 hp (29.75 kW)	39.9 hp (29.75 kW)
Displacement	899 cc	899 cc	999 cc	999 cc
Performance				
Operating Weight	1935 lb. (878 kg)	2165 lb. (982 kg)	1855 lb. (841 kg)	2085 lb. (945 kg)
Travel Speed (Max) - High	35 mph (56 km/hr.)	35 mph (56 km/hr.)	35 mph (56 km/hr.)	35 mph (56 km/hr.)
Travel Speed - Low	16 mph (25 km/hr.)	16 mph (25 km/hr.)	25 mph (40 km/hr.)	25 mph (40 km/hr.)
Travel Speed - Reverse	16 mph (25 km/hr.)	16 mph (25 km/hr.)	25 mph (40 km/hr.)	25 mph (40 km/hr.)
Capacities				
Fuel Tank	11.5 gal. (43.5 L)	11.5 gal. (43.5 L)	11.5 gal. (43.5 L)	11.5 gal. (43.5 L)
Cargo Box Length	43.5 in. (1105 mm)	43.5 in. (1105 mm)	43.5 in. (1105 mm)	43.5 in. (1105 mm)
Cargo Box Width	54 in. (1372 mm)	54 in. (1372 mm)	54 in. (1372 mm)	54 in. (1372 mm)
Cargo Box Bed Load Capacity	1250 lb. (567 kg)	1250 lb. (567 kg)	1250 lb. (567 kg)	1250 lb. (567 kg)
Cargo Box Height	11.5 in. (292 mm)	11.5 in. (292 mm)	11.5 in. (292 mm)	11.5 in. (292 mm)
Cargo Box Bed Load Height	38 in. (965 mm)	38 in. (965 mm)	38 in. (965 mm)	38 in. (965 mm)
Vehicle Rated Capacity*	1900 lb. (862 kg)	2075 lb. (941 kg)	1900 lb. (862 kg)	2075 lb. (941 kg)
Dimensions				
Length	123 in. (3124 mm)	155 in. (3937 mm)	123 in. (3124 mm)	155 in. (3937 mm)
Width	62 in. (1575 mm)	62 in. (1575 mm)	62 in. (1575 mm)	62 in. (1575 mm)
Height	76 in. (1930 mm)	76 in. (1930 mm)	76 in. (1930 mm)	76 in. (1930 mm)
Ground Clearance	11.7 in. (296 mm)	11.7 in. (296 mm)	11.7 in. (296 mm)	11.7 in. (296 mm)
Turning Radius	120 in. (3048 mm)	168 in. (4267 mm)	120 in. (3048 mm)	168 in. (4267 mm)
Features				
Under-Seat Storage	Std	Std	Std	Std
Seat Belt	3-point, retractable	3-point, retractable	3-point, retractable	3-point, retractable
Power Steering	Std	Std	Std	Std
ROPS Approval	Std	Std	Std	Std
Brush Guard	Opt	Opt	Opt	Opt
Hour Meter	Std	Std	Std	Std
Speedometer	Std	Std	Std	Std
Tilt Steering Wheel	Std	Std	Std	Std
Bed Lift	Manual	Manual	Manual	Manual
Frame Type	Steel	Steel	Steel	Steel
Receiver Hitch	2"	2"	2"	2"
Front Suspension	Independent	Independent	Independent	Independent
Rear Suspension	Independent	Independent	Independent	Independent
Headlights	Std	Std	Std	Std
Drive System				
Transmission Type	P-R-N-L-H	P-R-N-L-H	P-R-N-L-H	P-R-N-L-H
Traction Type	4x4	4x4	4x4	4x4
4WD Selection	Switch	Switch	Switch	Switch
Differential Lock	Switch	Switch	Switch	Switch

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

*Vehicle Rated Capacity includes cargo box load, weight of occupant(s) and the weight of any accessories.



YOU ARE ONE TOUGH ANIMAL.

Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.



Bobcat is a Doosan company. Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering, proudly serving customers and communities for more than a century.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2020 Bobcat Company. All rights reserved.



MAQUINAS Y EQUIPOS AVANZADOS, S.A.
Calzada Atanasio Tz'ul 22-00 Zona 12
Empresarial El Cortijo II. Bodega 229, Guatemala, Guatemala
PBX: 2294-8700
www.maqsa.gt



Bobcat®

One Tough Animal.